

T-FIT[®]

INSULATION

Fit to perform. **Fit** to last


T-FIT[®] Process

**Best-in-class
high-performance
insulation for
demanding high-
temperature
processing
environments**

- High-temperature performance
- Wide operating temperature range (-20°C to +200°C)
- Robust and durable
- Hydrophobic, bacteria-resistant (ASTM G21-15 certified)
- Resistant to most chemicals
- Integral aluminium cladding
- Automotive industry approvals



T-FIT® Process is stable up to 200°C (EN14707), making it the insulation of choice for process areas such as steam lines, food processes, energy, electronic, photonic and chemical applications. Integral aluminium cladding offers the highest level of physical protection around hot pipe works.



A unique combination of in-use performance benefits makes T-FIT® Process the logical choice wherever heat-tolerant insulation is important

Safest: T-FIT Process' closed-cell foam structure is highly resistant to bacteria and mould growth. It meets and exceeds the industry-standard ASTM G21-15 and is also fibre-, dust, and particulate-free.

Cleanest: T-FIT® Process's closed-cell structure is highly-resistant to bacteria and mould growth. It meets and exceeds the industry-standard ASTM G21-15 and is also fibre-, dust- and particulate-free.

Simplest: With an operating range of -80°C to +200°C, T-FIT® Process is suitable for both chilled and hot processing applications. For fast, tool-free installation, plus a long maintenance-free service life, T-FIT Process straights are easy to fabricate into elbows, bends etc. T-FIT Process is easy to remove, open and close for inspection, and is available in 12.7mm and 6.35mm thicknesses, depending on specification.

Most flexible: T-FIT® Process can be installed indoors, undercover or outside without loss of performance. The crosslinked structure easily withstands physical compression and other rigours associated with installation processes during construction work and while in service.

Most cost-effective: Reduced installation cost, smaller footprint, lower operating costs and a reduced risk of cross-contamination — add a long maintenance-free service life to these benefits for the lowest Total Cost of Ownership of any high-performance process insulation system.

Zotefoams plc

675 Mitcham Road
Croydon, Surrey
CR9 3AL, United Kingdom
Tel: +44 (0) 20 8664 1600
Email: t-fitsales@zotefoams.com

T-FIT Insulation Solutions India Private Limited

810 Shapath V, S.G. Highway
Ahmedabad, Gujarat, 380015
Tel: +91 (0) 7433946464
Email: t-fitindia@zotefoams.com

Zotefoams T-FIT Material Technology (Kunshan) Co., Ltd

181 Huanlou Road, Development Zone,
Kunshan City, Jiangsu Pr. China 215333
Tel: +86 (0) 512 5012 6001-8001
Email: t-fitchina@zotefoams.com

Zotefoams Inc.

55 Precision Drive
Walton KY, 41094 USA
Tel: +1 (0) 859 371 4025
Free: (800) 362-8358 (US Only)
Email: t-fitusa@zotefoams.com

T-FIT® and ZOTEK® are registered
trademarks of Zotefoams plc.
All rights reserved.

Issue 1 Revision 1
April 2021

If you would like more information visit our website www.zotefoams.com