

T-FIT® PVDF Tape

T-FIT®

INSULATION

Fit to perform. **Fit** to last

T-FIT PVDF Tape technical information


This adhesive tape product is designed specifically for T-FIT® Installations. Comprised of a PVDF polymer film and a high-performance pressure sensitive adhesive. Especially designed for chemical and flammability resistance.

Product description

Item code: ZAXX9164

Roll construction

- 0.003" PVDF polymer film
- 0.003" white high-performance adhesive
- 80lb Kraft release liner
- Total Tape Thickness .011" (including release liner)



Roll dimensions

Current Product supplied as the following:

- 1" (25,4mm) wide x 60 linear yards long (54.8m)
- Supplied on a 3" plastic core
- Release liner facing outward, film inward

Tape format

- Standard format of solid back or non-split liner
- Also available as a "split-back" or 50/50 split release line

Technical information

Property (Per ASTM D903 Al Foil to Al Plate)	Minimum average	Maximum individual
Peel Strength (PIW) at 70°F ± 5°F plus 7 days after 7 days aging at 70°F ± 5°F	10	9
Peel Strength (PIW) 1 day at 70°F ± 5°F plus 6 days at 95 to 100% relative humidity at 120°F ± 5°F	15	14
Peel Strength (PIW) 1 day at 70°F ± 5°F plus 6 days exposure at 160°F ± 5°F	18.5 1	7.5

Static load creep properties (Per ASTM D903 Al Foil to Al Plate)	Creep time (hrs)	Minimum average	Maximum individual
Creep distance (inches per pound/inch of width) at 70°F ± 5°F plus 7 days after 7 days aging at 70°F ± 5°F	24	1	2
Creep distance (inches per pound/inch of width) 1 day at 70°F ± 5°F plus 6 days at 95 to 100% relative humidity at 120°F ± 5°F	24	1	2
Creep distance (inches per pound/inch of width) at 1 day at 70°F ± 5°F plus 6 days exposure at 160°F ± 5°F	24	0.5	2

Thermal performance

- Film & Adhesive is recommended to temperatures up to 212 °F / (100 °C)

Application notes

- Bonding surfaces must be clean and dry
- Once release liner is removed the tape must be applied immediately, with firm even pressure

Shelf life

- 18 months from date of manufacture

Regulatory data

- PVDF Film meets FDA 177.2510 & 177.2600 Repeated Contact with Food, 177.1520 Single-use Adjuvant for use in Polyolefins 1% Concentration

Exclusion of Liability

Any information contained in this document is, to the best of the knowledge and belief of Zotefoams plc and of Zotefoams Inc. (together herein referred to as ZOTEFOAMS), accurate. Any liability on the part of ZOTEFOAMS or any subsidiary or holding company of ZOTEFOAMS for any loss, damage, costs or expenses directly or indirectly arising out of the use of such information or the use, application, adaptation or processing of any goods, materials or products described herein is, save as provided in ZOTEFOAMS' conditions of sale ("Conditions of Sale"), hereby excluded to the fullest extent permitted by law.

Where ZOTEFOAMS' goods or materials are to be used in conjunction with other goods or materials, it is the responsibility of the user to obtain from the manufacturers or suppliers of the other goods or materials all technical data and other properties relating to those other goods or materials. Save as provided in the Conditions of Sale no liability can be accepted in respect of the use of ZOTEFOAMS' goods or materials in conjunction with any other goods or materials.

Where ZOTEFOAMS' goods or materials are likely to come into contact with foodstuffs or pharmaceuticals, whether directly or indirectly, or are likely to be used in the manufacture of toys, prior written confirmation of compliance with relevant legislative or regulatory standards for those applications may be requested from ZOTEFOAMS, if appropriate. Save as provided in the Conditions of Sale no liability can be accepted for any damage, loss or injury directly or indirectly arising out of any failure by the user to obtain such confirmation or to observe any recommendations given by or on behalf of ZOTEFOAMS.

ZOTEFOAMS MAKES NO WARRANTIES EXPRESS OR IMPLIED, EXCEPT TO THE EXTENT SET OUT IN THE CONDITIONS OF SALE, AND HEREBY SPECIFICALLY EXCLUDES ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ANY GOODS, MATERIALS OR PRODUCTS DESCRIBED HEREIN.

Zotefoams plc Management systems are covered by the following:



Quality
FM 01870
ISO 9001:2015



Safety
OHS 52538
ISO 45001: 2018



Environment
EMS 36270
ISO 14001:2015

Zotefoams plc

675 Mitcham Road
Croydon
Surrey
CR9 3AL
United Kingdom

Tel: +44 (0) 20 8664 1600
Email: t-fitsales@zotefoams.com

T-FIT Insulation Solutions India Private Limited

810 Shapath V, S.G. Highway
Ahmedabad
Gujarat
380015

Tel: +91 (0) 7433946464
Email: t-fitindia@zotefoams.com

Zotefoams T-FIT Material Technology (Kunshan) Co., Ltd

181 Huanlou Road
Development Zone,
Kunshan City,
Jiangsu Pr.
China 215333

Tel: +86 (0)512 5012 6001-8001
Email: t-fitchina@zotefoams.com

Zotefoams Inc.

55 Precision Drive
Walton KY
41094 USA

Tel: +1 (0) 859 371 4025
Free: (800) 362-8358 (US Only)
Email: t-fitusa@zotefoams.com

T-FIT® and ZOTEK® are registered trademarks of Zotefoams plc. Kynar® is a registered trademark of Arkema Inc. All rights reserved

Issue 1 Revision 1

If you would like more information visit our website www.zotefoams.com