



# ZOTEFOAMS

## Zotefoams plc

675 Mitcham Road  
Croydon  
CR9 3AL  
UK

t +44 (0)20 8664 1600  
f +44 (0)20 8664 1616  
e [info@zotefoams.com](mailto:info@zotefoams.com)  
[www.zotefoams.com](http://www.zotefoams.com)

February 2024

## OFFICIAL STATEMENT

**STATE OF CALIFORNIA  
ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF ENVIRONMENTAL HEALTH HAZARD ASSESSMENT  
SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986  
CHEMICALS KNOWN TO THE STATE TO CAUSE CANCER OR REPRODUCTIVE  
TOXICITY  
(‘Proposition 65’)**

This is to confirm the status of the foam used in T-FIT® Hygiene, ZOTEK® F43 HT, regarding the use of substances listed in the California Proposition 65 list dated December 29<sup>th</sup> 2023. This statement covers the foam used in T-FIT® Hygiene products listed in Table 1 and Table 2.

**We can confirm that none of the substances listed in ‘Proposition 65’ are used or otherwise intentionally added during the current foam manufacturing process employed by Zotefoams plc for the production of our foam products stated above.**

It is important to note that this statement applies to the T-FIT products as they leave Zotefoams production facilities. Zotefoams will not accept liability for other materials or processes used in combination with T-FIT products.

We trust that the above statement is sufficient, however if any further information or clarification is required then please do not hesitate to contact the Technical Support group at the web address above.

Yours sincerely,

**Dr Karl Hewson  
Director of Technology and Development**



# ZOTEFOAMS

Table 1: List of T-FIT® Hygiene Products in 6.35 mm thickness

| Product Code        | T-FIT® Hygiene<br>Moulded from Zotek®F43HT, product length 960mm         | Product Internal Diameter |           |
|---------------------|--|---------------------------|-----------|
|                     |  | Imperial                  | Metric mm |
| TFHS012A06U000-9001 | ASME BPE 0.5" OD 12.7MM T-FIT Hygiene Insulating Straight 6.35mm THK     | 0.5"                      | 12.7      |
| TFHS019A06U000-9002 | ASME BPE 0.75" OD 19.0MM T-FIT Hygiene Insulating Straight 6.35mm THK    | 0.75"                     | 19        |
| TFHS025A06U000-9003 | ASME BPE 1.0" OD 25.40mm T-FIT Hygiene Insulating Straight 6.35mm THK    | 1"                        | 25.4      |
| TFHS038A06U000-9004 | ASME BPE 1.5" OD 38.10mm T-FIT Hygiene Insulating Straight 6.35mm THK    | 1.5"                      | 38.1      |
| TFHS050A06U000-9005 | ASME BPE 2.0" OD 50.80mm T-FIT Hygiene Insulating Straight 6.35mm THK    | 2"                        | 50.8      |
| TFHS063A06U000-9006 | ASME BPE 2.5" OD 63.50mm T-FIT Hygiene Insulating Straight 6.35mm THK    | 2.5"                      | 63.5      |
| TFHS076A06U000-9007 | ASME BPE 3.0" OD 76.20mm T-FIT Hygiene Insulating Straight 6.35mm THK    | 3"                        | 76.2      |
| TFHS101A06U000-9008 | ASME BPE 4.0" OD 101.60mm T-FIT Hygiene Insulating Straight 6.35mm THK   | 4"                        | 101.6     |
| TFHS021I06U000-9009 | ISO 1127 DN15 OD 21.3mm T-FIT Hygiene Insulating Straight 6.35mm THK     | DN15                      | 21.3      |
| TFHS026I06U000-9010 | ISO 1127 DN20 OD 26.9mm T-FIT Hygiene Insulating Straight 6.35mm THK     | DN20                      | 26.9      |
| TFHS033I06U000-9011 | ISO 1127 DN25 OD 33.7mm T-FIT Hygiene Insulating Straight 6.35mm THK     | DN25                      | 33.7      |
| TFHS042I06U000-9017 | ISO 1127 DN32 OD 42.4mm T-FIT Hygiene Insulating Straight 6.35mm THK     | DN32                      | 42.4      |
| TFHS048I06U000-9012 | ISO 1127 DN40 OD 48.3mm T-FIT Hygiene Insulating Straight 6.35mm THK     | DN40                      | 48.3      |
| TFHS060I06U000-9013 | ISO 1127 DN50 OD 60.3mm T-FIT Hygiene Insulating Straight 6.35mm THK     | DN50                      | 60.3      |
| TFHS076I06U000-9014 | ISO 1127 DN65 OD 76.1mm T-FIT Hygiene Insulating Straight 6.35mm THK     | DN65                      | 76.1      |
| TFHS088I06U000-9015 | ISO 1127 DN80 OD 88.9mm T-FIT Hygiene Insulating Straight 6.35mm THK     | DN80                      | 88.9      |
| TFHS114I06U000-9016 | ISO 1127 DN100 OD 114.3mm T-FIT Hygiene Insulating Straight 6.35mm THK   | DN100                     | 114.3     |
| TFHS023D06U000-9004 | DIN 11850 DN20 OD 23.00mm T-FIT Hygiene Insulating Straight 6.35mm THK   | DN20                      | 23        |
| TFHS029D06U000-9005 | DIN 11850 DN25 OD 29.00mm T-FIT Hygiene Insulating Straight 6.35mm THK   | DN25                      | 29        |
| TFHS035D06U000-9006 | DIN 11850 DN32 OD 35.00mm T-FIT Hygiene Insulating Straight 6.35mm THK   | DN32                      | 35        |
| TFHS041D06U000-9007 | DIN 11850 DN40 OD 41.00mm T-FIT Hygiene Insulating Straight 6.35mm THK   | DN40                      | 41        |
| TFHS053D06U000-9008 | DIN 11850 DN50 OD 53.00mm T-FIT Hygiene Insulating Straight 6.35mm THK   | DN50                      | 53        |
| TFHS070D06U000-9009 | DIN 11850 DN65 OD 70.00mm T-FIT Hygiene Insulating Straight 6.35mm THK   | DN65                      | 70        |
| TFHS085D06U000-9010 | DIN 11850 DN80 OD 85.00mm T-FIT Hygiene Insulating Straight 6.35mm THK   | DN80                      | 85        |
| TFHS104D06U000-9011 | DIN 11850 DN100 OD 104.00mm T-FIT Hygiene Insulating Straight 6.35mm THK | DN100                     | 104       |
| TFHS057G06U000-9006 | GB 12459 2.0" OD57.00mm T-FIT Hygiene Insulating Straight 6.35mm THK     | 2.0"                      | 57        |





# ZOTEFOAMS

Table 2: List of T-FIT Hygiene Products in 12.7 mm thickness

| Product Code        | T-FIT® Hygiene<br>Moulded from Zotek®F43HT, product length 960mm        | Product Internal Diameter |           |
|---------------------|---|---------------------------|-----------|
|                     |   | Imperial                  | Metric mm |
| TFHS025A12U000-9003 | ASME BPE 1.0" OD 25.40mm T-FIT Hygiene Insulating Straight 12.70mm THK  | 1"                        | 25.4      |
| TFHS038A12U000-9004 | ASME BPE 1.5" OD 38.10mm T-FIT Hygiene Insulating Straight 12.70mm THK  | 1.5"                      | 38.1      |
| TFHS050A12U000-9005 | ASME BPE 2.0" OD 50.80mm T-FIT Hygiene Insulating Straight 12.70mm THK  | 2"                        | 50.8      |
| TFHS063A12U000-9006 | ASME BPE 2.5" OD 63.50mm T-FIT Hygiene Insulating Straight 12.70mm THK  | 2.5"                      | 63.5      |
| TFHS076A12U000-9007 | ASME BPE 3.0" OD 76.20mm T-FIT Hygiene Insulating Straight 12.70mm THK  | 3"                        | 76.2      |
| TFHS101A12U000-9008 | ASME BPE 4.0" OD 101.60mm T-FIT Hygiene Insulating Straight 12.70mm THK | 4"                        | 101.6     |
| TFHS021I12U000-9009 | ISO 1127 DN15 OD 21.3mm T-FIT Hygiene Insulating Straight 12.7mm THK    | DN15                      | 21.3      |
| TFHS026I12U000-9010 | ISO 1127 DN20 OD 26.9mm T-FIT Hygiene Insulating Straight 12.7mm THK    | DN20                      | 26.9      |
| TFHS033I12U000-9011 | ISO 1127 DN25 OD 33.7mm T-FIT Hygiene Insulating Straight 12.7mm THK    | DN25                      | 33.7      |
| TFHS042I12U000-9017 | ISO 1127 DN32 OD 42.4mm T-FIT Hygiene Insulating Straight 12.7mm THK    | DN32                      | 42.4      |
| TFHS048I12U000-9012 | ISO 1127 DN40 OD 48.3mm T-FIT Hygiene Insulating Straight 12.7mm THK    | DN40                      | 48.3      |
| TFHS060I12U000-9013 | ISO 1127 DN50 OD 60.3mm T-FIT Hygiene Insulating Straight 12.7mm THK    | DN50                      | 60.3      |
| TFHS076I12U000-9014 | ISO 1127 DN65 OD 76.1mm T-FIT Hygiene Insulating Straight 12.7mm THK    | DN65                      | 76.1      |
| TFHS088I12U000-9015 | ISO 1127 DN80 OD 88.9mm T-FIT Hygiene Insulating Straight 12.7mm THK    | DN80                      | 88.9      |
| TFHS023D12U000-9004 | DIN 11850 DN20 OD 23.00mm T-FIT Hygiene Insulating Straight 12.7mm THK  | DN20                      | 23        |
| TFHS029D12U000-9005 | DIN 11850 DN25 OD 29.00mm T-FIT Hygiene Insulating Straight 12.7mm THK  | DN25                      | 29        |
| TFHS035D12U000-9006 | DIN 11850 DN32 OD 35.00mm T-FIT Hygiene Insulating Straight 12.7mm THK  | DN32                      | 35        |
| TFHS041D12U000-9007 | DIN 11850 DN40 OD 41.00mm T-FIT Hygiene Insulating Straight 12.7mm THK  | DN40                      | 41        |
| TFHS053D12U000-9008 | DIN 11850 DN50 OD 53.00mm T-FIT Hygiene Insulating Straight 12.7mm THK  | DN50                      | 53        |
| TFHS070D12U000-9009 | DIN 11850 DN65 OD 70.00mm T-FIT Hygiene Insulating Straight 12.7mm THK  | DN65                      | 70        |
| TFHS085D12U000-9010 | DIN 11850 DN80 OD 85.00mm T-FIT Hygiene Insulating Straight 12.7mm THK  | DN80                      | 85        |



Quality  
FM 01870  
ISO 9001:2015



Safety  
OHS 52538  
HSAS 18001:2007



Environment  
EMS 36270  
ISO 14001:2015