



ZOTEFOAMS

Zotefoams plc

675 Mitcham Road
Croydon
CR9 3AL
UK

t +44 (0)20 8664 1600

f +44 (0)20 8664 1616

e info@zotefoams.com

www.zotefoams.com

December 2023

OFFICIAL STATEMENT

*'DIRECTIVE 2011/65/EU and 2015/863/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL
of 8 June 2011*

*on the restriction of the use of certain hazardous substances in electrical and electronic equipment'
(recast)*

This is to confirm that the foam used in T-FIT® Hygiene, ZOTEK® F43 HT, is fully compliant with the requirements of the EC directive 2011/65/EU above (otherwise referred to as the 'RoHS' directive), the EC directive 2015/863/EU and all amendments to date. This statement covers the foam used in all T-FIT® Hygiene products which are listed in Table 1 and Table 2.

In particular I can advise that at no stage during the manufacturing process utilised by Zotefoams plc for the manufacture of the above products are the following substances or compounds of them intentionally added to the product formulation:

- **Lead (Pb)**
- **Mercury (Hg)**
- **Cadmium (Cd)**
- **Hexavalent Chromium (Cr6+)**
- **PolyBrominated Biphenyls (PBB) or PolyBrominated Diphenyl Ethers (PBDE)**
- **Phthalates (DEHP, BBP, DBP and DIBP)**

It is important to note that this statement applies to the T-FIT products as they leave Zotefoams production facilities. Zotefoams will not accept liability for other materials or processes used in combination with T-FIT products.

I trust that the above statement is sufficient, however if any further information or clarification is required then please do not hesitate to contact the Technical Support group at the address above.

Yours sincerely,

Dr. Karl Hewson
Director of Technology & Development



ZOTEFOAMS

Table 1: List of T-FIT® Hygiene Products in 6.35 mm thickness

Product Code	T-FIT® Hygiene		Product Internal Diameter	
	Moulded from Zotek®F43HT, product length 960mm		Imperial	Metric mm
TFHS012A06U000-9001	ASME BPE 0.5"	OD 12.7MM T-FIT Hygiene Insulating Straight 6.35mm THK	0.5"	12.7
TFHS019A06U000-9002	ASME BPE 0.75"	OD 19.0MM T-FIT Hygiene Insulating Straight 6.35mm THK	0.75"	19
TFHS025A06U000-9003	ASME BPE 1.0"	OD 25.40mm T-FIT Hygiene Insulating Straight 6.35mm THK	1"	25.4
TFHS038A06U000-9004	ASME BPE 1.5"	OD 38.10mm T-FIT Hygiene Insulating Straight 6.35mm THK	1.5"	38.1
TFHS050A06U000-9005	ASME BPE 2.0"	OD 50.80mm T-FIT Hygiene Insulating Straight 6.35mm THK	2"	50.8
TFHS063A06U000-9006	ASME BPE 2.5"	OD 63.50mm T-FIT Hygiene Insulating Straight 6.35mm THK	2.5"	63.5
TFHS076A06U000-9007	ASME BPE 3.0"	OD 76.20mm T-FIT Hygiene Insulating Straight 6.35mm THK	3"	76.2
TFHS101A06U000-9008	ASME BPE 4.0"	OD 101.60mm T-FIT Hygiene Insulating Straight 6.35mm THK	4"	101.6
TFHS021I06U000-9009	ISO 1127 DN15	OD 21.3mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN15	21.3
TFHS026I06U000-9010	ISO 1127 DN20	OD 26.9mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN20	26.9
TFHS033I06U000-9011	ISO 1127 DN25	OD 33.7mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN25	33.7
TFHS042I06U000-9017	ISO 1127 DN32	OD 42.4mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN32	42.4
TFHS048I06U000-9012	ISO 1127 DN40	OD 48.3mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN40	48.3
TFHS060I06U000-9013	ISO 1127 DN50	OD 60.3mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN50	60.3
TFHS076I06U000-9014	ISO 1127 DN65	OD 76.1mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN65	76.1
TFHS088I06U000-9015	ISO 1127 DN80	OD 88.9mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN80	88.9
TFHS114I06U000-9016	ISO 1127 DN100	OD 114.3mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN100	114.3
TFHS023D06U000-9004	DIN 11850 DN20	OD 23.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN20	23
TFHS029D06U000-9005	DIN 11850 DN25	OD 29.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN25	29
TFHS035D06U000-9006	DIN 11850 DN32	OD 35.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN32	35
TFHS041D06U000-9007	DIN 11850 DN40	OD 41.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN40	41
TFHS053D06U000-9008	DIN 11850 DN50	OD 53.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN50	53
TFHS070D06U000-9009	DIN 11850 DN65	OD 70.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN65	70
TFHS085D06U000-9010	DIN 11850 DN80	OD 85.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN80	85
TFHS104D06U000-9011	DIN 11850 DN100	OD 104.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN100	104
TFHS057G06U000-9006	GB 12459 2.0"	OD57.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	2.0"	57





ZOTEFOAMS

Table 2: List of T-FIT® Hygiene Products in 12.7 mm thickness

Product Code	T-FIT® Hygiene Moulded from Zotek®F43HT, product length 960mm	Product Internal Diameter	
		Imperial	Metric mm
TFHS025A12U000-9003	ASME BPE 1.0" OD 25.40mm T-FIT Hygiene Insulating Straight 12.70mm THK	1"	25.4
TFHS038A12U000-9004	ASME BPE 1.5" OD 38.10mm T-FIT Hygiene Insulating Straight 12.70mm THK	1.5"	38.1
TFHS050A12U000-9005	ASME BPE 2.0" OD 50.80mm T-FIT Hygiene Insulating Straight 12.70mm THK	2"	50.8
TFHS063A12U000-9006	ASME BPE 2.5" OD 63.50mm T-FIT Hygiene Insulating Straight 12.70mm THK	2.5"	63.5
TFHS076A12U000-9007	ASME BPE 3.0" OD 76.20mm T-FIT Hygiene Insulating Straight 12.70mm THK	3"	76.2
TFHS101A12U000-9008	ASME BPE 4.0" OD 101.60mm T-FIT Hygiene Insulating Straight 12.70mm THK	4"	101.6
TFHS021I12U000-9009	ISO 1127 DN15 OD 21.3mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN15	21.3
TFHS026I12U000-9010	ISO 1127 DN20 OD 26.9mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN20	26.9
TFHS033I12U000-9011	ISO 1127 DN25 OD 33.7mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN25	33.7
TFHS042I12U000-9017	ISO 1127 DN32 OD 42.4mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN32	42.4
TFHS048I12U000-9012	ISO 1127 DN40 OD 48.3mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN40	48.3
TFHS060I12U000-9013	ISO 1127 DN50 OD 60.3mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN50	60.3
TFHS076I12U000-9014	ISO 1127 DN65 OD 76.1mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN65	76.1
TFHS088I12U000-9015	ISO 1127 DN80 OD 88.9mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN80	88.9
TFHS023D12U000-9004	DIN 11850 DN20 OD 23.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN20	23
TFHS029D12U000-9005	DIN 11850 DN25 OD 29.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN25	29
TFHS035D12U000-9006	DIN 11850 DN32 OD 35.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN32	35
TFHS041D12U000-9007	DIN 11850 DN40 OD 41.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN40	41
TFHS053D12U000-9008	DIN 11850 DN50 OD 53.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN50	53
TFHS070D12U000-9009	DIN 11850 DN65 OD 70.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN65	70
TFHS085D12U000-9010	DIN 11850 DN80 OD 85.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN80	85

